



<u>Panels</u>

The Nylofor 3D Super system with specific 3D bend and very thick horizontal wires provides optimal protection and offers a unique design.

Product detail



BENEFITS

Very high Rigidity

The panels are extremely rigid due to the large wire diameters and the use of a specific 3D bend.

High degree of security

Nylofor 3D Super is the recommended fencing system when security is crucial.

Long lifetime

Betafence's coating technology guarantees a high longevity. After galvanising, a special layer is applied for a perfect adhesion of the polyester coating.

Complete system

The system offers panels in different heights, posts with adapted fixation systems and a large range of gates. All components guarantee a fast and professional installation.

Security level



Applications







Functionalities







Post and fixing systems

The Nylofor 3D Super system can be used with several posts systems:



Nylofor - Twilfix post system

The panels are fixed on the front side of the posts by means of fixators and security bolts. The welded square tubular posts (60 x 60 mm) have inserts for fixing the panels and are covered with a plastic cap. For installation higher than 2.40 m, post section can be 80x60 or 120x60. Square post system with bent arm: possible



Bekafix and Bekafix Ultra post system (with metal fixators)

The panels are fixed laterally onto the posts and secured with anti-vandal metal security fixators. The H-shape welded tubular posts (70 x 44 mm), are galvanised and PES coated an supplied complete with a polyamide cap and accessories.

For technical details on different post systems: cfr. specific pages on posts.

Panels

Heavy welded mesh, 2500 mm wide and available in different heights.

The panels have vertical barbs of 30 mm height on one side. Standard mesh: $200 \times 50 \text{ mm}$

Mesh of 3D bend: $200 \times 50 \text{ mm}$ Wire diameter:

Horizontal: 8.00 mm Vertical: 5.00 m

Gates

The Nylofor 3D Super system is completed by the Robusta swing and sliding gates and Bekamatic gates.

Coating technique

The panels are made out of galvanised wires. An adhesion coating is given for a perfect adhesion with the polyester coating (min.100 micron).

Colours

Nylofor 3D Super is standard available in green RAL 6005 More and other colours out of our RAL Collection are available on request.

ASSORTMENT NYLOFOR 3D SUPER		
Fence height	Panels width x height	Number of curves
mm	mm	per panel
1030	2500 x 1030	2
1630	2500 x 1630	3
2030	2500 x 2030	4
2430	2500 x 2430	4
3030	2500 x 3030	4

Other heights available on request

Europe
Blokkestraat 34b
B-8550 Zwevegem
Tel: B: +32 56 73 46 4

Tel: B: +32 56 73 46 46 Tel: NL: 0800 022 76 98 USA 3309 SW Interstate 45 Ennis, TX 75119

Tel: +1 972 878 7000

Middle East P.O. Box 293517 DAFZA, Building E 5, Block A 8th Floor, Office 802

Tel: +971 04 6091122

Africa B10, Bergriver Business Park Paarl, 7646

Tel: +27 021 868 7300



Betafence is the world market leader in fencing solutions, access control and detection for perimeter protection. All Betafence companies and product

names are trademarks owned by PRÆSIDIAD Group Limited. Modification in products and assortment are subject to change without prior notice.